

## EDC12-70 (12V 70Ah)

### Specifications

Nominal Voltage	12V	
Nominal Capacity(20 Hr)	70Ah	
Dimension	Length	350±1mm( 13.78 inches)
	Width	167±1mm( 6.57 inches)
	Container Height	178±1mm( 7.01 inches)
	Total Height (With terminal)	178±1mm( 7.01 inches)
	Approx Weight	Approx. 23.3kgs (51.37 lbs)
Design life	up to 12 years (in standby applications)	
Terminal	M6	
Container Material	ABS	
Rated Capacity	70.0Ah/3.50A	(20hr, 1.75V/Cell, 25 °C/77°F)
	65.0Ah/6.50A	(10hr, 1.80V/Cell, 25 °C/77°F)
	63.0Ah/12.6A	(5hr, 1.75V/Cell, 25 °C/77°F)
	41.7Ah/41.7A	(1hr, 1.60V/Cell, 25 °C/77°F)
Max. Discharge Current	700A(5s)	
Internal Resistance	Appro≤8.3mΩ	
Operating Temp. Range	Discharge:	-20 °C~50 °C
	Charge:	0 °C~40 °C
	Storage:	-20 °C~50 °C
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current Less than 15.75 A. Voltage 14.4V-15.0V at 25 °C(77°F ) Temp. Coefficient-20mV/C	
	Standby Use	
Capacity affected by Temperature	40 °C( 104°F )	103%
	25 °C( 77°F )	100%
	0 °C( 32°F )	86%
Self Discharge	EDC series batteries may be stored for up to 6 months at25 °C(77°F ) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



### Application

- ◆ All purpose
- ◆ Uninterruptable Power Supply(UPS)
- ◆ Electric Power System(EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and securitysystem
- ◆ Electronic apparatus & equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto controlsystem

### Constant Current Discharge (Amperes) at 25 °C ( 77F )




F.V/Time	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h	100h
1.60V	90.1	57.5	42.3	38.9	24.7	17.4	11.8	7.8	6.93	3.71	0.84
1.67V	88.5	56.5	41.5	38.2	24.2	17.0	11.6	7.6	6.79	3.64	0.83
1.70V	86.8	55.4	40.7	37.5	23.8	16.7	11.3	7.5	6.65	3.57	0.81
1.75V	85.2	54.4	40.0	36.8	23.3	16.4	11.1	7.4	6.58	3.50	0.79
1.80V	81.9	52.3	38.4	35.4	22.4	15.8	10.7	7.1	6.37	3.47	0.78

### Constant Power Discharge (Watts) at 25 °C ( 77F )


F.V/Time	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h	100h
1.60V	173.4	110.7	81.4	74.7	47.5	33.3	22.7	14.9	13.4	7.2	1.62
1.67V	170.2	108.7	79.9	73.4	46.6	32.8	22.3	14.7	13.1	7.1	1.58
1.70V	167.1	106.7	78.4	72.0	45.8	32.1	21.8	14.4	12.9	7.0	1.55
1.75V	163.9	104.7	76.9	70.6	44.9	31.5	21.4	14.1	12.6	6.9	1.53
1.80V	157.6	100.7	74.0	67.9	43.2	30.3	20.7	13.6	12.1	6.7	1.50

**EDC12-70 (12V 70Ah)**


**Dimensions**




**Discharge Characteristics**




**Float Charging Characteristics**




**Temperature Effects in Relation to Battery Capacity**




**Effect of Temperature on Long Term Float Life**



**Cycle life in Relation to Depth of Discharge**



**Self-discharge Characteristics**



Specifications subject to change without prior notice.