

ODS-AGM6M (PC2250)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V
Capacity (20-hour rate)	126Ah
Capacity (10-hour rate)	92Ah
Cold Cranking Amps (CCA, SAE J537)	1225A
PHCA - 5-second pulse current	2250A
HCA	1730A
MCA	1550A
Reserve capacity	240 mins
Short circuit current (using IEC method)	5000A
Internal resistance at 20°C (using IEC method)	$2.1~\text{m}\Omega$

Dimensions & Weight

Length	287 mm
Width	269 mm
Height (to top of terminals)	234 mm
Height Container	0 mm
Weight	39 kg

Temperature

Operating Temperature Range	-40°C to +40°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 07/04/2022 11:19:56 Information correct at time of exporting PDF. Please check website for updates.



EnerSysWorld Headquarters 2366 Bernville Road EH Reading, PA 19605,USA Bar Tel: +1-610-208-1991 / +1-800-538-3627 Sw

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780

Extreme AGM TO SHAPE TO SHAPE

Terminal Position

Terminal Type

