


BATTERY CHARGER

SCI90 ⚡ 6/12V 🔌 90A



+++

Fully automatic microprocessor-controlled charger

Auto voltage detection (6/12V)

150A boost mode to help start dead batteries

Deep desulfation mode

Built-in digital voltmeter/tester – shows battery voltage & charging percentage

Float mode monitoring maintains optimum battery charge

Patented thermal runaway protection, monitors charge process to prevent battery from over heating

Reverse hook-up protection
Helps protect battery and charger from damage

Protection against reverse polarity

Protection against reverse polarity



TECHNICAL INFORMATION

MODEL	SCI90
PART NUMBER	94065007C
VOLTAGE (DC)	6/12V
VARIABLE CHARGE RATES	3 A / 5 A / 20 A
MAX. CHARGING CURRENT	90 A - 150 A
ENGINE START MODE (EMERGENCY STARTING)	√
CABLE LENGTH	1,75 m
BATTERY TYPES	AGM, GEL , CALCIUM AND SULFATED BATTERIES



PACKAGING INFORMATION

MODEL	SCI90
NET WEIGHT	5,82 kg
DIMENSIONS (L x W x H / mm)	232 x 258 x 171

RELATED PART NUMBER:

FOOT FOR RUBBER BASE

4999000171



 Rue de la Baronnerie, 3
4920 Harzé - Belgium

+32 4 388 20 17

 info@schumachereurope.com
www.schumachereurope.com

 @schumacherboosters

Since
1947

#passionatesince1947